



Materials

Barrel: Brass, Gold plated
Spring: Music Wire, Silver o Gold plated
Plunger: Steel or Hardened Beryllium copper,
Gold over Hard Nickel

Technical Data

Recommended Minimum Centers: 2,54 mm
Current Rating: 2,0-3,0 A
Typical Contact Resistance: 20 mΩ
Recommended Working Travel: 6,40 mm
Max Travel: GLP 422: 8,00 mm - GLP 212: 10,00 mm
Spring Force: 200g - 100g - 150g - 250g - 300g

Ø mm	2,00	1,30 2,00	2,00	0,60	1,40 2,00	2,00	2,00	1,30 2,00	1,02 1,30	1,02 1,30	1,30 2,00	1,30 2,00	1,02
Head													
Material	B	B	B-S	B-S	B-S	B	B-S	B-S	S	S	B-S	B-S	B-S

Receptacle GLR 422 - GLR 212
See page 15

ORDERING EXAMPLE:

GLP 422	B	21	180	200	G
Model	Material	Tip Style	Tip Diameter	Spring Force	Plating

Order info:
Material Plating
B=BeCu G=Gold
S=Steel N=Nickel

GENTEC TEST
ZA Les Sablons
F 77230 Dammartin en Goële
Tel: +33 1 60 27 07 76 / +33 1 60 03 91 91
Fax: +33 1 60 03 91 70
Web: www.gentec-test.com
e-mail: sales@gentec-test.com

Dimensions in Millimeters

Additional configurations on request - Specifications subject to change