



**Materials**

Barrel: Brass, Gold plated  
Spring: Music Wire, Silver o Gold plated  
Plunger: Steel or Hardened Beryllium copper,  
Gold over Hard Nickel

**Technical Data**

Recommended Minimum Centers: 2,54 mm  
Current Rating: 2,0-3,0 A  
Typical Contact Resistance: 20 mΩ  
Recommended Working Travel: 6,40 mm  
Max Travel: GLP 422: 8,00 mm - GLP 212: 10,00 mm  
Spring Force: 200g - 100g - 150g - 250g - 300g

Ø mm	2,00	1,30 2,00	2,00	0,60	1,40 2,00	2,00	2,00	1,30 2,00	1,02 1,30	1,02 1,30	1,30 2,00	1,30 2,00	1,02
Head													
Material	B	B	B-S	B-S	B-S	B	B-S	B-S	S	S	B-S	B-S	B-S

**Receptacle GLR 422 - GLR 212**  
See page 15

ORDERING EXAMPLE:

GLP 422	B	21	180	200	G
Model	Material	Tip Style	Tip Diameter	Spring Force	Plating

Order info:  
Material      Plating  
B=BeCu      G=Gold  
S=Steel      N=Nickel

GENTEC TEST  
ZA Les Sablons  
F 77230 Dammartin en Goële  
Tel: +33 1 60 27 07 76 / +33 1 60 03 91 91  
Fax: +33 1 60 03 91 70  
Web: www.gentec-test.com  
e-mail: sales@gentec-test.com

Dimensions in Millimeters

Additional configurations on request - Specifications subject to change